



Industrial Hot Water Fully Electrically Heated

Pumps (General Pumps)

- Industrial Heavy Duty Triplex Plunger Pumps • Oil Bath Crank Case
- Stainless Valves • Brass Manifold • Thermo Pump Protector • Belt Or Flange & Coupling Driven

Electric Motors (3, 5, 7.5, 10 & 20 HP)

- 1750 RPM • TEFC • Full Frame • 1.25 Service Factors • Thermo Overload Protection • Continuous Duty • Rated Premium Efficiency

Heater

- 316 Stainless Steel Heat Exchanger Coil • Designed For Continuous Use
- Large 70 Gallon (Single Coil Models) & 120 Gallon (Dual Coil Models) Heater Storage Tanks • Allows for Continuous Recovery Even When Trigger Gun (s) Not in Use • No Open Flame • Can be Installed in Virtually Any Location • Compact Foot Print • Standard and Explosion Proof Models • No Venting Required • Heater Exchanger Coils Do Not Require Decalcification • Require Less KW Than Input Direct-immersion Type Electrically Heated Models • Low water Heat Exchanger Solution Cut-Off Switch • Adjustable Temperature Controller • Pin- Type Calrod Heating Elements With Incoloy Sleeves

Frame

- All Welded - Powder Coated • 11 Gauge Bent Steel Tip Ahead Shroud Designed To Expose All Components for Ease of Service

Includes

- Liquid Filled Pressure Gauge • Adjustable Pressure Regulator • 48" Gun and Wand Assembly with Quick Coupler System • 0°/15°/25°/40° Nozzles • 50 Feet of High Pressure Wash Hoses (8 - 10 GPM Units Include 2 Gun & Wand Assemblies & 50 Feet of High Pressure Hose)

Options & Accessories

- Full Range of Portable Frames • Stainless Steel Covers and Heater Skins • 50HZ Models • ASME B31.1 • 2004 (Power Piping) Code • Compliant Models Available And Explosion Proof Units.
- VFD • PLC Control • Remote Control

*Utilized by:
Mines, Mills,
Refineries,
Service Shops
and Food
Processing
Plants.*

** Offer Units
With Double
Coils*



MODEL	GPM	PSI	HEATER INPUT	MOTOR HP	TOTAL AMP 3PH			Dimensions L" x W" x H"
					208	460	575	
PJE114E24A	4	1200	24KW	3	72.5	33.3	26.6	32x24x52
PJE114E48A	4	1200	48KW	3	134.8	62.2	49.7	32x24x52
PJE204E24	4	2000	24KW	5	77.1	35.5	28.4	32x24x52
PJE204E48A	4	2000	48KW	5	139.6	64.4	51.8	32x24x52
PJE204E72A	4	2000	72KW	5	N/A	93.3	74.4	32x24x52
PJE304E24A	4	3000	24KW	7.5	85	39.1	31.3	32x24x52
PJE304E48A	4	3000	48KW	7.5	147.5	68	54.4	32x24x52
PJE304E72A	4	3000	72KW	7.5	N/A	96.5	76.9	32x24x52
PJE404E48A	4	4000	48KW	10	154	70.9	56.7	32x24x52
PJE404E72A	4	4000	72KW	10	N/A	99.8	79.9	32x24x52
PJE504E48A	4	5000	48KW	15	N/A	75.9	60.7	38x28x55
PJE504E72A	4	5000	72KW	15	N/A	104.8	83.9	38x28x55
PJE505E48A	5	5000	48KW	20	N/A	82.8	66.5	38x28x55
PJE505E72A	5	5000	72KW	20	N/A	112.2	89.8	38x28x55
PJE355E48A	5	3500	48KW	10	154	70.9	56.7	32x24x52
PJE355E72A	5	3500	72KW	10	N/A	99.8	79.9	32x24x52
PJE256E48A	5.6	2000	48KW	7.5	147.5	68	54.4	32x24x52
PJE256E72A	5.6	2000	72KW	7.5	N/A	96.9	77.6	32x24x52
PJE126E48A	6	1200	48KW	5	139.6	64.4	51.8	32x24x52
PJE206E48A*	6	2000	48KW	10	147.5	68	54.4	53x48x40
PJE206E72A*	6	2000	72KW	10	N/A	96.9	77.6	53x48x40
PJE1208E48A*	8	1200	48KW	7.5	147.5	68	54.4	53x48x40
PJE1208E72A*	8	1200	72KW	7.5	N/A	96.9	77.6	53x48x40
PJE208E48A*	8	2000	48KW	10	154	70.9	56.7	53x48x40
PJE208E72A*	8	2000	72KW	10	N/A	99.8	79.9	53x48x40
PJE308E48A*	8	3000	48KW	15	165	75.9	60.7	53x48x40
PJE308E72A*	8	3000	72KW	15	N/A	104.8	83.9	53x48x40
PJE3010E72A*	10	3000	72KW	20	N/A	112.2	89.8	53x48x40
PJE3010E96A*	10	3000	96KW	20	N/A	141.3	113.1	53x48x40
PJE3010E115A*	10	3000	115KW	20	N/A	164.3	131.4	53x48x40